

# MULTI LOCK STEEL TIE COATED



## Application

- Suitable for corrosive climate condition, higher temperature and higher tensile strength requirement



## Key Industries

- Aerospace ● Chemicals & Refineries ● Dairy & Food Processing ● Oil, Gas & Offshore ● Ship & Marines ● Solar ● Telecom ● Utility ● Windmills

## Specification

- Material:** Stainless Steel SS 316, SS 304  
**Coating Material:**
  - Black Polyester-Polyester
  - Black Nylon-Nylon**Operating Temp:** -80°C to +150°C  
**Installation:** By tie tools (STT 1 & 2) & hook (STT 3)  
**Test Certificate:**  
**Packing:** 100 pcs bag  
**Unit:** 100 Pcs/Pkt

## Features

- Multi lock steel ties are self locking with multiple locking systems designed for strong and secure hold
- It is designed to accommodate double wraps
- Smooth edges of ties provide utmost safety while installation
- Coating material is non-toxic, halogen free, low smoke and UV resistant
- Coated ties provide long term life in corrosive climate condition

Dimension In MM				Dimension In Inch				Coating Type	Loop Tensile Strength (kgs)/(lbs)	G.W. /100 pcs (Kgs)/(Lbs)	Cat. No. SS 316	Cat No. SS 304
Length	Width	Thickness	Max. Bundle Dia	Length	Width	Thickness	Max. Bundle Dia					
150	7.0	0.40	35	5.91	0.28	0.02	1.38	Polyester	60 (132)	0.28 (0.61)	ML-150CP	ML-150/4CP
150	7.0	0.50	35	5.91	0.28	0.02	1.38	Nylon	60 (132)	0.28 (0.61)	ML-150CN	ML-150/4CN
225	7.0	0.40	60	8.86	0.28	0.02	2.36	Polyester	60 (132)	0.36 (0.79)	ML-225CP	ML-225/4CP
225	7.0	0.50	60	8.86	0.28	0.02	2.36	Nylon	60 (132)	0.36 (0.79)	ML-225CN	ML-225/4CN
300	7.0	0.40	80	11.81	0.28	0.02	3.15	Polyester	60 (132)	0.45 (0.99)	ML-300CP	ML-300/4CP
300	7.0	0.50	80	11.81	0.28	0.02	3.15	Nylon	60 (132)	0.45 (0.99)	ML-300CN	ML-300/4CN
450	7.0	0.40	125	17.72	0.28	0.02	4.92	Polyester	60 (132)	0.64 (1.41)	ML-450CP	ML-450/4CP
450	7.0	0.50	125	17.72	0.28	0.02	4.92	Nylon	60 (132)	0.64 (1.41)	ML-450CN	ML-450/4CN
610	7.0	0.40	180	24.02	0.28	0.02	7.09	Polyester	60 (132)	0.85 (1.87)	ML-610CP	ML-610/4CP
610	7.0	0.50	180	24.02	0.28	0.02	7.09	Nylon	60 (132)	0.85 (1.87)	ML-610CN	ML-610/4CN
150	12.0	0.40	35	5.91	0.47	0.02	1.38	Polyester	130 (287)	0.49 (1.08)	MLH-150CP	MLH-150/4CP
150	12.0	0.50	35	5.91	0.47	0.02	1.38	Nylon	130 (287)	0.49 (1.08)	MLH-150CN	MLH-150/4CN
225	12.0	0.40	60	8.86	0.47	0.02	2.36	Polyester	130 (287)	0.64 (1.41)	MLH-225CP	MLH-225/4CP
225	12.0	0.50	60	8.86	0.47	0.02	2.36	Nylon	130 (287)	0.64 (1.41)	MLH-225CN	MLH-225/4CN
300	12.0	0.40	80	11.81	0.47	0.02	3.15	Polyester	130 (287)	0.83 (1.82)	MLH-300CP	MLH-300/4CP
300	12.0	0.50	80	11.81	0.47	0.02	3.15	Nylon	130 (287)	0.83 (1.82)	MLH-300CN	MLH-300/4CN
450	12.0	0.40	125	17.72	0.47	0.02	4.92	Polyester	130 (287)	1.17 (2.57)	MLH-450CP	MLH-450/4CP
450	12.0	0.50	125	17.72	0.47	0.02	4.92	Nylon	130 (287)	1.17 (2.57)	MLH-450CN	MLH-450/4CN
610	12.0	0.40	180	24.02	0.47	0.02	7.09	Polyester	130 (287)	1.63 (3.59)	MLH-610CP	MLH-610/4CP
610	12.0	0.50	180	24.02	0.47	0.02	7.09	Nylon	130 (287)	1.63 (3.59)	MLH-610CN	MLH-610/4CN